



DIMENSION	TQ/HT100			TQ/HT144			TQ/HT176		
	MILLIMETERS			MILLIMETERS			MILLIMETERS		
	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.	MIN.	NOM.	MAX.
A	\approx	\approx	1.60	\approx	\approx	1.60	\approx	\approx	1.60
A ₁	0.05	\approx	0.15	0.05	0.10	0.15	0.05	0.10	0.15
A ₂	1.35	1.40	1.45	1.35	1.40	1.45	1.35	1.40	1.45
D/E	16.00 BSC			22.00 BSC			26.00 BSC		
D ₁ /E ₁	14.00 BSC			20.00 BSC			24.00 BSC		
L	0.45	0.60	0.75	0.45	0.60	0.75	0.45	0.60	0.75
e	0.50 BSC			0.50 BSC			0.50 BSC		
b	0.17	0.22	0.27	0.17	0.22	0.27	0.17	0.22	0.27
c	0.09	\approx	0.20	0.09	\approx	0.20	0.09	\approx	0.20
ccc	\approx	\approx	0.08	\approx	\approx	0.08	\approx	\approx	0.08
ddd	\approx	\approx	0.08	\approx	\approx	0.08	\approx	\approx	0.08
N	100			144			176		
REF.	JEDEC MS-026-BED			JEDEC MS-026-BFB			JEDEC MS-026-BGA		

DETAIL 'A'

NOTE:

- ALL DIMENSIONS AND TOLERANCES CONFORM TO ANSI Y14.5-1994
- DIMENSION D₁ AND E₁ DO NOT INCLUDE MOLD PROTRUSION. ALLOWABLE MOLD PROTRUSION SHALL NOT EXCEED 0.25mm PER SIDE.
- PACKAGE TOP DIMENSION MAY BE SMALLER THAN THE BOTTOM DIMENSION BY 0.15mm.

△ THE SAME PACKAGE DIMENSIONS APPLY FOR THERMALLY ENHANCED PRODUCTS. HEAT SINK IS ADDED. THE PACKAGE CODE IS "HT".
 HEAT SINK DIMENSIONS: HT100=10.0mm SQ. REF.
 HT144=15.5mm SQ. REF.
 HT176=19.4mm SQ. REF.

△ MARK ORIENTATION WITH RESPECT TO PIN-1 I.D.
 IF 2 OR MORE CIRCLES EXIST ON TOP OF THE PACKAGE, USE THE SMALLEST CIRCLE AS PIN-1 I.D.